

# Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations SDS Reference Number: 1300703

Issue date: 4/9/2019 Revision date: 5/29/2025 Version: 1.1

## **SECTION 1 Identification**

#### 1.1. Product identifier

Product form : Substance

Substance name : 1-Chloro-1-fluoroethylene, high purity

 CAS-No.
 : 2317-91-1

 Product code
 : 1300-7-03H

 Formula
 : C2H2CIF

#### 1.2. Other means of identification

Other means of identification : MFCD00042129 EC-No. : 219-027-6

#### 1.3. Recommended use of the chemical and restrictions on use

Use of the substance/mixture : Laboratory chemicals, Manufacture of substances, Scientific research and development

#### 1.4. Supplier's details

SynQuest Laboratories, Inc.

P.O. Box 309

Alachua, FL, Alachua, 32615 United States of America

T (386) 462-0788 - F (386) 462-7097

info@synquestlabs.com - www.synquestlabs.com

## 1.5. Emergency phone number

Emergency number : (844) 523-4086 (3E Company - Account 10069)

### **SECTION 2 Hazard Identification**

### 2.1. Classification of the substance or mixture

#### **GHS US classification**

Flammable gases, Category 2 H221 Flammable gas.

Gases under pressure: Liquefied gas H280 Contains gas under pressure; may explode if heated.

Skin corrosion/irritation, Category 2

Serious eye damage/eye irritation, Category 2A

Specific target organ toxicity – Single exposure, Category 3, Narcosis

Specific target organ toxicity – Single exposure, Category 3, Narcosis

Specific target organ toxicity – Single exposure, Category 3, Narcosis

Specific target organ toxicity – Single exposure, Category 3, Narcosis

May cause drowsiness or dizziness.

May cause respiratory irritation.

Respiratory tract irritation

Full text of H statements : see section 16

### 2.2. Label elements

## **GHS US labeling**

Hazard pictograms (GHS US)





Signal word (GHS US) : Warning

Hazard statements (GHS US) : H221 - Flammable gas

H280 - Contains gas under pressure; may explode if heated

# Safety Data Sheet

Precautionary statements (GHS US)

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

H315 - Causes skin irritation

H319 - Causes serious eye irritation

H335 - May cause respiratory irritation

H336 - May cause drowsiness or dizziness

: P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking

P261 - Avoid breathing fumes, gas, mist, spray, vapors.

P264 - Wash hands, forearms and face thoroughly after handling.

P271 - Use only outdoors or in a well-ventilated area.

P280 - Wear protective gloves.

P302+P352 - If on skin: Wash with plenty of soap and water

P304+P340 - If inhaled: Remove person to fresh air and keep comfortable for breathing.

P305+P351+P338 - If in eyes: Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing

P312 - Call a POISON CENTER or doctor/physician if you feel unwell

P321 - Specific treatment (see supplemental first aid instruction on this label).

P332+P313 - If skin irritation occurs: Get medical advice or attention. P337+P313 - If eye irritation persists: Get medical advice or attention.

P362+P364 - Take off contaminated clothing and wash it before reuse.

P377 - Leaking gas fire: Do not extinguish, unless leak can be stopped safely.

P381 - In case of leakage, eliminate all ignition sources.

P403 - Store in a well-ventilated place.

P403+P233 - Store in a well-ventilated place. Keep container tightly closed.

P405 - Store locked up.

P410+P403 - Protect from sunlight. Store in a well-ventilated place.

P501 - Dispose of contents and/or container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulations.

#### 2.3. Hazards associated with known or reasonably anticipated uses

No additional information available

## 2.4. Hazards not otherwise classified

Other hazards which do not result in classification : May cause frostbite.

## 2.5. Unknown acute toxicity

No additional information available

#### **SECTION 3 Composition/information on ingredients**

#### 3.1. Substances

Substance type : Mono-constituent

Name	Product identifier	%	GHS US classification
1-Chloro-1-fluoroethylene, high purity (Main constituent)	CAS-No.: 2317-91-1	≤ 100	Flam. Gas 2, H221 Press. Gas (Liq.), H280 Skin Irrit. 2, H315 Eye Irrit. 2A, H319 STOT SE 3, H336 STOT SE 3, H335

Full text of hazard classes and H-statements : see section 16

#### 3.2. Mixtures

Not applicable

# Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

#### **SECTION 4 First aid measures**

#### 4.1. Description of necessary first-aid measures

First-aid measures general

First-aid measures after inhalation Remove person to fresh air and keep comfortable for breathing. If not breathing, give artificial

respiration. Get immediate medical advice/attention.

First-aid measures after skin contact Thaw frosted parts with lukewarm water. Do not rub affected area. Get immediate medical

advice/attention.

First-aid measures after eye contact Remove contact lenses, if present and easy to do. Continue rinsing. Immediately flush eyes thoroughly with water for at least 15 minutes. Get immediate medical advice/attention.

Due to its physical form, exposure to this chemical is not likely. Do NOT induce vomiting. Never

give anything by mouth to an unconscious person. Rinse mouth out with water. Get medical advice/attention.

: In case of accident or if you feel unwell, seek medical advice immediately (show the label where

possible). Move the affected personnel away from the contaminated area.

## 4.2. Most important symptoms/effects, acute and delayed

Symptoms/effects : The most important known symptoms and effects are described in the labelling (see section 2.2) and/or in section 11.

Symptoms/effects after inhalation May cause drowsiness or dizziness.

Symptoms/effects after skin contact Contact with the liquid the may cause cold burns/frostbite.

Symptoms/effects after eye contact Direct contact with the liquefied gas may cause severe and possibly permanent eye injury due to frostbite from rapid liquid evaporation.

### 4.3. Indication of immediate medical attention and special treatment needed, if necessary

No additional information available

First-aid measures after ingestion

## **SECTION 5: Fire-fighting measures**

#### 5.1. Suitable (and unsuitable) extinguishing media

Suitable extinguishing media : Alcohol resistant foam. Carbon dioxide. Dry powder. Water spray. Use extinguishing media appropriate for surrounding fire.

#### 5.2. Specific hazards arising from the chemical

Fire hazard : Thermal decomposition generates: Carbon oxides. Hydrogen chloride. Hydrogen fluoride.

Explosion hazard Contains gas under pressure; may explode if heated. Use water spray or fog for cooling exposed containers. May form flammable/explosive vapor-air mixture.

#### 5.3. Special protective equipment and precautions for fire-fighters

Firefighting instructions : In case of fire: Evacuate area. Fight fire remotely due to the risk of explosion.

Protection during firefighting : Wear gas tight chemically protective clothing in combination with self contained breathing apparatus. For further information refer to section 8: "Exposure controls/personal protection".

## **SECTION 6 Accidental release measures**

#### 6.1. Personal precautions, protective equipment and emergency procedures

General measures : Evacuate unnecessary personnel. Ensure adequate air ventilation. May cause suffocation by reducing oxygen available for breathing. Do not breathe gas, fumes, vapor or spray.

For non-emergency personnel

**Emergency procedures** : Only qualified personnel equipped with suitable protective equipment may intervene.

5/29/2025 (Revision date) EN (English US) 3/10

# Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

#### For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer

to section 8: "Exposure controls/personal protection".

Emergency procedures : Gas/vapor heavier than air. May accumulate in confined spaces, particularly at or below ground

level. Consider the risk of potentially explosive atmospheres. Eliminate every possible source of

ignition.

Environmental precautions : Avoid release to the environment. Notify authorities if product enters sewers or public waters.

#### 6.2. Methods and materials for containment and cleaning up

For containment : Stop leak if safe to do so.

Methods for cleaning up : Ventilate area.

Other information : For disposal of solid materials or residues refer to section 13 : "Disposal considerations".

For further information refer to section 8: "Exposure controls/personal protection"

# **SECTION 7 Handling and storage**

#### 7.1. Precautions for safe handling

Precautions for safe handling : Do not handle until all safety precautions have been read and understood. Ensure good

ventilation of the work station. Do not breathe fumes, gas, mist, spray, vapors. Wear personal protective equipment. Avoid contact with skin and eyes. Keep away from ignition sources (including static discharges). Proper grounding procedures to avoid static electricity should be

followed. Use only non-sparking tools.

Hygiene measures : Handle in accordance with good industrial hygiene and safety procedures. Do not eat, drink or

smoke when using this product. Always wash hands after handling the product.

Additional hazards when processed : Pressurized container: Do not pierce or burn, even after use. Handle empty containers with care

because residual vapors are flammable. Close valve after each use and when empty.

#### 7.2. Conditions for safe storage, including incompatibilities

Technical measures : Comply with applicable regulations.

Storage conditions : Protect from sunlight. Do not expose to temperatures exceeding 50 °C. Keep container closed

when not in use. Keep away from ignition sources.

Storage area : Store in dry, cool, well-ventilated area.

Incompatible materials : Refer to Section 10 on Incompatible Materials.

#### **SECTION 8 Exposure controls/personal protection**

#### 8.1. Control parameters

No additional information available

## 8.2. Appropiate engineering controls

Appropriate engineering controls

: Ensure good ventilation of the work station. Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure. Systems under pressure should be regularily checked for leakage. Oxygen detectors should be used when asphyxiating gases may be released.

# 8.3. Individual protection measures, such as personal protective equipment

#### Hand protection:

protective gloves. 29 CFR 1910.138: Hand Protection

5/29/2025 (Revision date) EN (English US) 4/10

# Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

#### Eye protection:

Chemical goggles or safety glasses. Face shield. 29 CFR 1910.133: Eye and Face Protection

#### Skin and body protection:

Wear suitable protective clothing

#### Respiratory protection:

In case of inadequate ventilation wear respiratory protection. 29 CFR 1910.134: Respiratory Protection

#### Personal protective equipment symbol(s):









## Thermal hazard protection:

Cold insulating gloves.

#### Other information:

Safety shoes. 29 CFR 1910.136: Foot Protection.

# **SECTION 9 Physical and chemical properties**

#### 9.1. Basic physical and chemical properties

Physical state : Gas

Color: No data availableOdor: No data availableOdor threshold: No data availablepH: No data available

Melting point : -169 °C

Freezing point : No data available

Boiling point : -24 °C

: No data available Flash point : No data available Flammability (solid, gas) Vapor pressure 67 psia (@ 7 °C) Relative vapor density at 20 °C : No data available Relative density : No data available : 1.098 g/ml Density : 80.489 g/mol Molecular mass Solubility : No data available Partition coefficient n-octanol/water (Log Pow) : No data available Auto-ignition temperature : No data available Decomposition temperature : No data available Viscosity, kinematic : No data available **Explosion limits** : No data available Particle characteristics : No data available

## 9.2. Data relevant with regard to physical hazard classes (supplemental)

No additional information available

## **SECTION 10 Stability and reactivity**

#### 10.1. Reactivity

No additional information available

# Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

#### 10.2. Chemical stability

The product is stable at normal handling and storage conditions.

## 10.3. Possibility of hazardous reactions

May polymerize.

#### 10.4. Conditions to avoid

Protect from sunlight. Do not expose to temperatures exceeding 50 °C. Keep away from heat, sparks and flame.

#### 10.5. Incompatible materials

Alkali metals. Finely divided metals (Al, Mg, Zn). Strong oxidizing agents.

#### 10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced. Hazardous decomposition products in case of fire, see Section 5.

# **SECTION 11 Toxicological information**

## 11.1. Likely routes of exposure

Acute toxicity (oral) : No data available
Acute toxicity (dermal) : No data available
Acute toxicity (inhalation) : No data available
Skin corrosion/irritation : Causes skin irritation.

Serious eye damage/irritation : Causes serious eye irritation.

Respiratory or skin sensitization : No data available Germ cell mutagenicity : No data available

Carcinogenicity : No data available

Reproductive toxicity : No data available

STOT-single exposure : May cause drowsiness or dizziness. May cause respiratory irritation.

STOT-repeated exposure : No data available
Aspiration hazard : Not applicable

Symptoms/effects : The most important known symptoms and effects are described in the labelling (see section 2.2)

and/or in section 11.

Symptoms/effects after inhalation : May cause drowsiness or dizziness.

Symptoms/effects after skin contact : Contact with the liquid the may cause cold burns/frostbite.

Symptoms/effects after eye contact : Direct contact with the liquefied gas may cause severe and possibly permanent eye injury due to

frostbite from rapid liquid evaporation.

# **SECTION 12 Ecological information**

## 12.1. Ecotoxicity

Hazardous to the aquatic environment, short-term : No da

(acute

Hazardous to the aquatic environment, long-term

(chronic)

: No data available

: No data available

5/29/2025 (Revision date) EN (English US) 6/10

# Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

#### 12.2. Persistence and degradability

#### 1-Chloro-1-fluoroethylene, high purity (2317-91-1)

Persistence and degradability Rapidly degradable

## 12.3. Bioaccumulative potential

No additional information available

## 12.4. Mobility in soil

No additional information available

#### 12.5. Other adverse effects

Ozone : No data available

Fluorinated greenhouse gases : No

## **SECTION 13 Disposal considerations**

Waste treatment methods : Remove to an authorized incinerator equipped with an afterburner and a flue gas scrubber.

Product/Packaging disposal recommendations : Dispose of contents/container in accordance with licensed collector's sorting instructions.

Additional information : Recycle the material as far as possible.

## **SECTION 14 Transport information**

### 14.1. UN number

 UN-No. (DOT)
 : UN3161

 UN-No. (TDG)
 : UN3161

 UN-No. (IMDG)
 : 3161

 UN-No. (IATA)
 : 3161

## 14.2. UN Proper Shipping Name

Proper Shipping Name (DOT) : Liquefied gas, flammable, n.o.s.

Proper Shipping Name (TDG) : LIQUEFIED GAS, FLAMMABLE, N.O.S.

Proper Shipping Name (IMDG) : LIQUEFIED GAS, FLAMMABLE, N.O.S.

Proper Shipping Name (IATA) : Liquefied gas, flammable, n.o.s.

## 14.3. Transport hazard class(es)

#### DOT

Transport hazard class(es) (DOT) : 2.1 Hazard labels (DOT) : 2.1



#### TDG

Transport hazard class(es) (TDG) : 2.1 Hazard labels (TDG) : 2.1



# Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

#### **IMDG**

Transport hazard class(es) (IMDG) : 2.1 Hazard labels (IMDG) : 2.1



#### **IATA**

Transport hazard class(es) (IATA) : 2.1 Hazard labels (IATA) : 2.1



## 14.4. Packing group

Packing group (DOT): Not applicablePacking group (TDG): Not applicablePacking group (IMDG): Not applicablePacking group (IATA): Not applicable

#### 14.5. Environmental hazards

Other information : No supplementary information available.

### 14.6. Transport in bulk

Not applicable

## 14.7. Special precautions for user

DOT

UN-No.(DOT) : UN3161

DOT Special Provisions (49 CFR 172.102) : T50 - When portable tank instruction T50 is referenced in Column (7) of the 172.101 Table, the

applicable liquefied compressed gases are authorized to be transported in portable tanks in

accordance with the requirements of 173.313 of this subchapter.

DOT Packaging Exceptions (49 CFR 173.xxx) : 306
DOT Packaging Non Bulk (49 CFR 173.xxx) : 304
DOT Packaging Bulk (49 CFR 173.xxx) : 314, 315
DOT Quantity Limitations Passenger aircraft/rail (49 : Forbidden

CFR 173.27)

DOT Quantity Limitations Cargo aircraft only (49

CFR 175.75)

: 150 kg

DOT Vessel Stowage Location : D - The material must be stowed "on deck only" on a cargo vessel and on a passenger vessel

carrying a number of passengers limited to not more than the larger of 25 passengers or one passenger per each 3 m of overall vessel length, but the material is prohibited on passenger

vessels in which the limiting number of passengers is exceeded.

DOT Vessel Stowage Other : 40 - Stow "clear of living quarters"

**TDG** 

UN-No. (TDG) : UN3161

5/29/2025 (Revision date) EN (English US) 8/10

# Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

**TDG Special Provisions** 

: 16 - 1) The technical name of the most dangerous substance related to the primary class must be shown, in parentheses, on the shipping document following the shipping name in accordance with clause 3.5(1)(c)(i)(A) of Part 3, Documentation. The technical name must also be shown, in parentheses, on a small means of containment or on a tag following the shipping name in accordance with subsections 4.11(2) and (3) of Part 4, Dangerous Goods Safety Marks.

2) subsection (1), the technical name for the following dangerous goods is not required to be shown on a shipping document or on a small means of containment when Canadian law for domestic transport or an international convention for international transport prohibits the disclosure of the technical: a) UN1544, ALKALOID SALTS, SOLID, N.O.S. or ALKALOIDS, SOLID, N.O.S; b) UN1851, MEDICINE, LIQUID, TOXIC, N.O.S; c) UN3140, ALKALOID SALTS, LIQUID, N.O.S. or ALKALOIDS, LIQUID, N.O.S; d) UN3248, MEDICINE, LIQUID, FLAMMABLE, TOXIC, N.O.S; or e) UN3249, MEDICINE, SOLID, TOXIC, N.O.S. An example in Canada is the "Food and Drugs Act".

ERAP Index : 3000

Explosive Limit and Limited Quantity Index : 0.125 L

Excepted quantities (TDG) : E0

Passenger Carrying Vessel Index : Forbidden

Passenger Carrying Road Vehicle or Passenger : Forbidden

Carrying Railway Vehicle Index

Emergency Response Guide (ERG) Number : 115

**IMDG** 

 Special provision (IMDG)
 : 274

 Limited quantities (IMDG)
 : 0

 Excepted quantities (IMDG)
 : E0

 Packing instructions (IMDG)
 : P200

 Tank instructions (IMDG)
 : T50

EmS-No. (Fire) : F-D - FIRE SCHEDULE Delta - FLAMMABLE GASES

EmS-No. (Spillage) : S-U - SPILLAGE SCHEDULE Uniform - GASES (FLAMMABLE, TOXIC OR CORROSIVE)

Stowage category (IMDG) : D
Stowage and handling (IMDG) : SW2

IATA

Special provision (IATA) : A1, A807 PCA Excepted quantities (IATA) : E0 Forbidden PCA Limited quantities (IATA) PCA limited quantity max net quantity (IATA) : Forbidden PCA packing instructions (IATA) Forbidden PCA max net quantity (IATA) Forbidden CAO packing instructions (IATA) : 200 CAO max net quantity (IATA) : 150kg ERG code (IATA) : 10L

## **SECTION 15 Regulatory information**

#### 15.1. Federal regulations

All components of this product are present and listed as Active on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory, except for:

1-Chloro-1-fluoroethylene, high purity CAS-No. 2317-91-1 100%

#### 15.2. International regulations

#### CANADA

No additional information available

5/29/2025 (Revision date) EN (English US) 9/10

# Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

#### **EU-Regulations**

## 1-Chloro-1-fluoroethylene, high purity (2317-91-1)

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)

#### **National regulations**

#### 1-Chloro-1-fluoroethylene, high purity (2317-91-1)

Listed on the Japanese ISHL (Industrial Safety and Health Law)

## 15.3. State regulations

California Proposition 65 - This product does not contain any substances known to the state of California to cause cancer, developmental and/or reproductive harm

#### **SECTION 16 Other information**

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Revision date : 5/29/2025 Issue date : 4/9/2019


Full text of hazard classes and H-statements	
H221	Flammable gas
H280	Contains gas under pressure; may explode if heated
H315	Causes skin irritation
H319	Causes serious eye irritation
H335	May cause respiratory irritation
H336	May cause drowsiness or dizziness

NFPA health hazard : 2 - Materials that, under emergency conditions, can cause temporary incapacitation or residual injury.

NFPA fire hazard : 3 - Liquids and solids (including finely divided suspended solids) that can be ignited under almost all ambient temperature conditions.

NFPA reactivity : 1 - Materials that in themselves are normally stable but can become

unstable at elevated temperatures and pressures.



Hazard Rating

Physical

Health : 2 Moderate Hazard - Temporary or minor injury may occur

Flammability : 3 Serious Hazard - Materials capable of ignition under almost all normal temperature conditions. Includes flammable liquids with flash points below 73 F and boiling points above 100 F. as well

as liquids with flash points between 73 F and 100 F. (Classes IB IC)

: 1 Slight Hazard - Materials that are normally stable but can become unstable (self-react) at high temperatures and pressures. Materials may react non-violently with water or undergo hazardous

polymerization in the absence of inhibitors.

Safety Data Sheet (SDS), USA

The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. The information in this document is based on the present state of our knowledge and is offered solely for your consideration, investigation, and verification. It does not represent any guarantee of the properties of the product nor that the hazard precautions or procedures described are the only ones which exist. SynQuest shall not be held liable or any damage resulting from handling or from contact with the above product.