



## SynQuest Laboratories, Inc.

PO Box 309, Alachua, FL 32616-0309

Tel. 386/462-0788; FAX 386/462-7097

# Material Safety Data Sheet

Transportation Emergency: 1-800-451-8346

Date last revised: November 2, 2011

Date printed: November 2, 2011

### SECTION 1. ----- CHEMICAL IDENTIFICATION-----

CATALOG #: 2801-7-01  
NAME: 2-CHLORO-3-HYDROXYBENZOTRIFLUORIDE  
SYNONYM: 2-CHLORO-3-(TRIFLUOROMETHYL)PHENOL

### SECTION 2. ----- COMPOSITION/INFORMATION ON INGREDIENTS -----

CAS NUMBER: 138377-34-1  
MOLECULAR FORMULA: C<sub>7</sub>H<sub>4</sub>ClF<sub>3</sub>O  
MOLECULAR WEIGHT: 196.55

### SECTION 3. ----- HAZARDS IDENTIFICATION -----

LABEL PRECAUTIONARY STATEMENTS  
COMBUSTIBLE (USA) FLAMMABLE (EU).  
IRRITANT.  
IRRITATING TO EYES, RESPIRATORY SYSTEM AND SKIN.

### SECTION 4. ----- FIRST-AID MEASURES-----

ORAL EXPOSURE  
IF SWALLOWED, WASH OUT MOUTH WITH WATER PROVIDED PERSON IS CONSCIOUS. CALL A PHYSICIAN.  
INHALATION EXPOSURE  
IF INHALED, REMOVE TO FRESH AIR. IF NOT BREATHING GIVE ARTIFICIAL RESPIRATION. IF BREATHING IS DIFFICULT, GIVE OXYGEN.  
DERMAL EXPOSURE  
IN CASE OF CONTACT, IMMEDIATELY WASH SKIN WITH SOAP AND COPIOUS AMOUNTS OF WATER.  
EYE EXPOSURE  
IN CASE OF CONTACT, IMMEDIATELY FLUSH EYES WITH COPIOUS AMOUNTS OF WATER FOR AT LEAST 15 MINUTES.

**SECTION 5. ----- FIRE FIGHTING MEASURES -----**

FLASH POINT

79 °C

EXTINGUISHING MEDIA

SUITABLE: FOR SMALL (INCIPIENT) FIRES, USE MEDIA SUCH AS "ALCOHOL" FOAM, DRY CHEMICAL, OR CARBON DIOXIDE. FOR LARGE FIRES, APPLY WATER FROM AS FAR AS POSSIBLE. USE VERY LARGE QUANTITIES (FLOODING) OF WATER APPLIED AS A MIST OR SPRAY; SOLID STREAMS OF WATER MAY BE INEFFECTIVE. COOL ALL AFFECTED CONTAINERS WITH FLOODING QUANTITIES OF WATER.

FIREFIGHTING

PROTECTIVE EQUIPMENT: WEAR SELF-CONTAINED BREATHING APPARATUS AND PROTECTIVE CLOTHING TO PREVENT CONTACT WITH SKIN AND EYES.

SPECIFIC HAZARD(S): COMBUSTIBLE LIQUID. EMITS TOXIC FUMES UNDER FIRE CONDITIONS.

**SECTION 6. ----- ACCIDENTAL RELEASE MEASURES-----**

PROCEDURE(S) OF PERSONAL PRECAUTION(S)

WEAR RESPIRATOR, CHEMICAL SAFETY GOGGLES, RUBBER BOOTS, AND HEAVY RUBBER GLOVES.

METHODS FOR CLEANING UP

COVER WITH DRY LIME OR SODA ASH, PICK UP, KEEP IN A CLOSED CONTAINER, AND HOLD FOR WASTE DISPOSAL. VENTILATE AREA AND WASH SPILL SITE AFTER MATERIAL PICKUP IS COMPLETE.

**SECTION 7. ----- HANDLING AND STORAGE-----**

HANDLING

USER EXPOSURE: DO NOT BREATHE VAPOR. AVOID CONTACT WITH EYES, SKIN, AND CLOTHING. AVOID PROLONGED OR REPEATED EXPOSURE.

STORAGE

SUITABLE: KEEP TIGHTLY CLOSED. KEEP AWAY FROM HEAT AND OPEN FLAME. STORE IN A COOL, DRY PLACE.

**SECTION 8. ----- EXPOSURE CONTROLS/PERSONAL PROTECTION-----**

ENGINEERING CONTROLS

SAFETY SHOWER AND EYE BATH. MECHANICAL EXHAUST REQUIRED.

PERSONAL PROTECTIVE EQUIPMENT

RESPIRATORY: USE RESPIRATORS AND COMPONENTS TESTED AND APPROVED UNDER APPROPRIATE GOVERNMENT STANDARDS SUCH AS NIOSH (US) OR CEN (EU). WHERE RISK ASSESSMENT SHOWS AIR-PURIFYING RESPIRATORS ARE APPROPRIATE USE A FULL-FACE RESPIRATOR WITH MULTI-PURPOSE COMBINATION (US) OR TYPE ABEK (EN 14387) RESPIRATOR CARTRIDGES AS A BACKUP TO ENGINEERING CONTROLS. IF THE RESPIRATOR IS THE SOLE MEANS OF PROTECTION, USE A FULL-FACE SUPPLIED AIR RESPIRATOR.

HAND: COMPATIBLE CHEMICAL-RESISTANT GLOVES.

EYE: CHEMICAL SAFETY GOGGLES.

GENERAL HYGIENE MEASURES

WASH THOROUGHLY AFTER HANDLING. WASH CONTAMINATED CLOTHING BEFORE REUSE.

**SECTION 9. ----- PHYSICAL AND CHEMICAL PROPERTIES -----**

APPEARANCE AND ODOR

COLORLESS TO FAINTLY YELLOW LIQUID

PHYSICAL PROPERTIES

BOILING POINT	160 °C
DENSITY	1.479 g/cm <sup>3</sup>
FLASH POINT	79 °C METHOD: CLOSED CUP
REFRACTIVE INDEX	1.473

**SECTION 10. -----STABILITY AND REACTIVITY -----**

STABILITY

MATERIALS TO AVOID: STRONG OXIDIZING AGENTS.

HAZARDOUS DECOMPOSITION PRODUCTS

HAZARDOUS DECOMPOSITION PRODUCTS: CARBON MONOXIDE, CARBON DIOXIDE, HYDROGEN CHLORIDE GAS, HYDROGEN FLUORIDE.

**SECTION 11. ----- TOXICOLOGICAL INFORMATION -----**

ROUTE OF EXPOSURE

SKIN CONTACT: SEVERE IRRITATION OR BURNS. CAUSES SKIN IRRITATION.

MULTIPLE ROUTES: VAPOR OR MIST IS IRRITATING TO THE EYES, MUCOUS MEMBRANES, AND UPPER RESPIRATORY TRACT. MAY BE HARMFUL BY INHALATION, INGESTION, OR SKIN ABSORPTION.

TARGET ORGAN(S) OR SYSTEM(S)

POSSIBLE DAMAGE TO THE EYES.

SIGNS AND SYMPTOMS OF EXPOSURE

DAMAGE TO THE EYES. PROLONGED CONTACT CAN CAUSE: DEPENDING ON THE INTENSITY AND DURATION OF EXPOSURE, EFFECTS MAY VARY FROM MILD IRRITATION TO SEVERE DESTRUCTION OF TISSUE.

**SECTION 12. ----- ECOLOGICAL INFORMATION -----**

DATA NOT YET AVAILABLE.

**SECTION 13. ----- DISPOSAL CONSIDERATIONS -----**

APPROPRIATE METHOD OF DISPOSAL OF SUBSTANCE OR PREPARATION

THIS COMBUSTIBLE MATERIAL MAY BE BURNED IN A CHEMICAL INCINERATOR EQUIPPED WITH AN AFTERBURNER AND SCRUBBER. OBSERVE ALL FEDERAL, STATE, AND LOCAL ENVIRONMENTAL REGULATIONS.

**SECTION 14. ----- TRANSPORT INFORMATION -----**

DOT

UNRESTRICTED

**SECTION 15. ----- REGULATORY INFORMATION -----**

EU ADDITIONAL CLASSIFICATION

SYMBOL OF DANGER: Xi

INDICATION OF DANGER: IRRITANT.

R: 10-36/37/38

S: 16-23-26-36/37/39

UNITED STATES REGULATORY INFORMATION

TSCA: NOT LISTED ON TSCA INVENTORY; FOR R&D USE ONLY

**SECTION 16. ----- OTHER INFORMATION-----**

THE ABOVE INFORMATION IS BELIEVED TO BE CORRECT BUT DOES NOT PURPORT TO BE ALL INCLUSIVE AND SHALL BE USED ONLY AS A GUIDE. SYNQUEST LABS, INC. SHALL NOT BE HELD LIABLE FOR ANY DAMAGE RESULTING FROM HANDLING OR FROM CONTACT WITH THE ABOVE PRODUCT.