

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations SDS ID: 4156328

Issue date: 05.10.2023 Version: 1.0

#### **SECTION 1: Identification**

#### 1.1. Identification

Product form : Substance

Substance name : Dimethylcarbamyl fluoride

CAS-No. : 431-14-1
Product code : 4156-3-28
Formula : C3H6FNO

#### 1.2. Recommended use and restrictions on use

Use of the substance/mixture : Laboratory chemicals

Manufacture of substances

Scientific research and development

#### 1.3. Supplier

SynQuest Laboratories, Inc. Inc.

P.O. Box 309

Alachua, FL, Alachua, 32615 United States of America

T (386) 462-0788 - F (386) 462-7097

info@synquestlabs.com - www.synquestlabs.com

#### 1.4. Emergency telephone number

Emergency number : (844) 523-4086 (3E Company - Account 10069)

#### **SECTION 2: Hazard(s) identification**

#### 2.1. Classification of the substance or mixture

#### **GHS US classification**

Flammable liquids Category 3 H226 Flammable liquid and vapor Acute toxicity (oral) Category 3 H301 Toxic if swallowed
Acute toxicity (dermal) Category 3 H311 Toxic in contact with skin Acute toxicity (inhalation) Category 3 H331 Toxic if inhaled

Skin corrosion/irritation Category 1B H314 Causes severe skin burns and eye damage

Serious eye damage/eye irritation Category 1 H318 Causes serious eye damage Specific target organ toxicity – Single exposure, Category 3, H335 May cause respiratory irritation

Respiratory tract irritation

Full text of H statements : see section 16

#### 2.2. GHS Label elements, including precautionary statements

#### **GHS US labeling**

Hazard pictograms (GHS US)









Signal word (GHS US) Hazard statements (GHS US) : Danger

: H226 - Flammable liquid and vapor

H301+H311+H331 - Toxic if swallowed, in contact with skin or if inhaled

H314 - Causes severe skin burns and eye damage

#### Safety Data Sheet

Precautionary statements (GHS US)

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

H318 - Causes serious eye damage

H335 - May cause respiratory irritation

 P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P233 - Keep container tightly closed.

P240 - Ground/Bond container and receiving equipment.

P241 - Use explosion-proof electrical/ventilating/lighting equipment

P242 - Use only non-sparking tools.

P243 - Take precautionary measures against static discharge.

P260 - Do not breathe fumes, mist, spray, vapors.

P264 - Wash skin thoroughly after handling

P270 - Do not eat, drink or smoke when using this product.

P271 - Use only outdoors or in a well-ventilated area.

P280 - Wear protective gloves/protective clothing/eye protection/face protection.

P301+P310 - If swallowed: Immediately call a poison center or doctor.

P301+P330+P331 - If swallowed: rinse mouth. Do NOT induce vomiting.

P302+P352 - If on skin: Wash with plenty of soap and water

P303+P361+P353 - If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

P304+P340 - If inhaled: Remove person to fresh air and keep comfortable for breathing.

P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove

contact lenses, if present and easy to do. Continue rinsing.

P310 - Immediately call a POISON CENTER or doctor/ physician

P311 - Call a POISON CENTER or doctor/physician

P321 - Specific treatment (see supplemental first aid instructions on this label)

P322 - Specific treatment (see supplemental first aid instruction on this label)

P330 - Rinse mouth.

P361+P364 - Take off immediately all contaminated clothing and wash it before reuse.

P363 - Wash contaminated clothing before reuse.

P370+P378 - In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish

P403+P233 - Store in a well-ventilated place. Keep container tightly closed.

P403+P235 - Store in a well-ventilated place. Keep cool.

P405 - Store locked up.

P501 - Dispose of contents/container to an approved waste disposal plant

#### 2.3. Other hazards which do not result in classification

Other hazards which do not result in classification : Lachrymator.

#### 2.4. Unknown acute toxicity (GHS US)

No additional information available

#### **SECTION 3: Composition/Information on ingredients**

#### 3.1. Substances

Substance type : Mono-constituent

Name	Product identifier	%	GHS US classification
Dimethylcarbamyl fluoride (Main constituent)	CAS-No.: 431-14-1		Flam. Liq. 3, H226 Acute Tox. 3 (Oral), H301 Acute Tox. 3 (Dermal), H311 Acute Tox. 3 (Inhalation), H331 Skin Corr. 1B, H314 Eye Dam. 1, H318 STOT SE 3, H335

Full text of hazard classes and H-statements : see section 16

#### Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

#### 3.2. Mixtures

Not applicable

#### **SECTION 4: First-aid measures**

#### 4.1. Description of first aid measures

First-aid measures general

: In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible). Move the affected personnel away from the contaminated area.

First-aid measures after inhalation

: Remove person to fresh air and keep comfortable for breathing. If not breathing, give artificial respiration. Get immediate medical advice/attention.

First-aid measures after skin contact

: Wash with plenty of soap and water. Remove contaminated clothing and shoes. In case of skin contact, wearing rubber gloves rub 2.5% calcium gluconate gel continuously into the affected area for 1.5 hours or until further medical care is available. Get immediate medical advice/attention.

First-aid measures after eye contact

: Immediately flush eyes thoroughly with water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get immediate medical advice/attention.

First-aid measures after ingestion

Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Rinse mouth out with water. Get immediate medical advice/attention.

#### 4.2. Most important symptoms and effects (acute and delayed)

Potential Adverse human health effects and symptoms

Symptoms/effects

: Absorption of excessive F- can result in acute systemic fluorosis with hypocalcemia, interference with various metabolic functions and organ damage (heart, liver, kidneys).

Symptoms/effects after inhalation

: The most important known symptoms and effects are described in the labelling (see section 2.2) and/or in section 11.

: Material is destructive to tissue of the mucuous membranes and upper respiratory tract. Cough, shortness of breath, headache, nausea.

#### 4.3. Immediate medical attention and special treatment, if necessary

Treat symptomatically. Absorption of excessive F- can result in acute systemic fluorosis with hypocalcemia, interference with various metabolic functions and organ damage (heart, liver, kidneys).

#### **SECTION 5: Fire-fighting measures**

#### 5.1. Suitable (and unsuitable) extinguishing media

Suitable extinguishing media : Dry powder. Use extinguishing media appropriate for surrounding fire.

#### 5.2. Specific hazards arising from the chemical

Fire hazard Explosion hazard

- : Thermal decomposition generates: Carbon oxides. Hydrogen fluoride. Nitrogen oxides.
- : Risk of explosion if heated under confinement. Use water spray or fog for cooling exposed containers. May form flammable/explosive vapor-air mixture.

#### 5.3. Special protective equipment and precautions for fire-fighters

Firefighting instructions

: In case of fire: Evacuate area. Fight fire remotely due to the risk of explosion.

Protection during firefighting

: Wear gas tight chemically protective clothing in combination with self contained breathing apparatus. For further information refer to section 8: "Exposure controls/personal protection".

05.10.2023 (Issue date) EN (English US) 3/11

#### Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

#### **SECTION 6: Accidental release measures**

#### 6.1. Personal precautions, protective equipment and emergency procedures

General measures : Evacuate unnecessary personnel. Ensure adequate air ventilation. Do not breathe gas, fumes,

vapor or spray.

6.1.1. For non-emergency personnel

Emergency procedures : Only qualified personnel equipped with suitable protective equipment may intervene.

6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer

to section 8: "Exposure controls/personal protection".

Emergency procedures : Gas/vapor heavier than air. May accumulate in confined spaces, particularly at or below ground

level. Consider the risk of potentially explosive atmospheres. Eliminate every possible source of

ignition.

#### 6.2. Environmental precautions

Avoid release to the environment. Notify authorities if product enters sewers or public waters.

#### 6.3. Methods and material for containment and cleaning up

For containment : Stop leak if safe to do so. Dike for recovery or absorb with appropriate material.

Methods for cleaning up : Take up large spills with pump or vacuum and finish with dry chemical absorbent. Use explosion-

proof equipment. Take up small spills with dry chemical absorbent. Sweep or shovel spills into appropriate container for disposal. Ventilate area.

Other information : For disposal of solid materials or residues refer to section 13 : "Disposal considerations".

#### 6.4. Reference to other sections

No additional information available

#### **SECTION 7: Handling and storage**

#### 7.1. Precautions for safe handling

Additional hazards when processed : Handle empty containers with care because residual vapors are flammable.

Precautions for safe handling

: Do not handle until all safety precautions have been read and understood. Ensure good ventilation of the work station. Do not breathe fumes, mist, spray, vapors. Wear personal protective equipment. Avoid contact with skin and eyes. Keep away from ignition sources (including static discharges). Proper grounding procedures to avoid static electricity should be

followed. Use only non-sparking tools.

Hygiene measures : Handle in accordance with good industrial hygiene and safety procedures. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

Shoke when using this product. Always wash hards after harding

#### 7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Comply with applicable regulations.

Storage conditions : Keep container closed when not in use. Keep away from ignition sources. Moisture sensitive.

Keep contents under inert gas.

Incompatible materials : Refer to Section 10 on Incompatible Materials.

Storage area : Store in dry, cool, well-ventilated area.

#### **SECTION 8: Exposure controls/personal protection**

#### 8.1. Control parameters

05.10.2023 (Issue date) EN (English US) 4/11

#### Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

#### Dimethylcarbamyl fluoride (431-14-1)

No additional information available

#### 8.2. Appropriate engineering controls

Appropriate engineering controls

: Ensure good ventilation of the work station. Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure.

#### 8.3. Individual protection measures/Personal protective equipment

#### Hand protection:

protective gloves. 29 CFR 1910.138: Hand Protection

#### Eye protection:

Chemical goggles or safety glasses. Face shield. 29 CFR 1910.133: Eye and Face Protection

#### Skin and body protection:

Wear suitable protective clothing

#### Respiratory protection:

In case of inadequate ventilation wear respiratory protection. 29 CFR 1910.134: Respiratory Protection

#### Personal protective equipment symbol(s):









#### Other information:

Safety shoes. 29 CFR 1910.136: Foot Protection.

#### **SECTION 9: Physical and chemical properties**

#### 9.1. Information on basic physical and chemical properties

Physical state : Liquid

Color : No data available
Odor : No data available
Odor threshold : No data available
pH : No data available
Melting point : No data available
Freezing point : No data available

Boiling point : 85 - 89 °C (@ 200 mm Hg)

Flash point : No data available
Relative evaporation rate (butyl acetate=1) : No data available
Flammability (solid, gas) : No data available
Vapor pressure : No data available
Relative vapor density at 20 °C : No data available
Relative density : No data available

Molecular mass : 91,085

Solubility : No data available
Partition coefficient n-octanol/water (Log Pow) : No data available
Auto-ignition temperature : No data available
Decomposition temperature : No data available
Viscosity, kinematic : No data available
Viscosity, dynamic : No data available

#### Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Explosion limits : No data available
Explosive properties : No data available
Oxidizing properties : No data available

#### 9.2. Other information

No additional information available

#### **SECTION 10: Stability and reactivity**

#### 10.1. Reactivity

No additional information available

#### 10.2. Chemical stability

The product is stable at normal handling and storage conditions.

#### 10.3. Possibility of hazardous reactions

Contact with acids liberates toxic gas. Contact with water liberates toxic gas.

#### 10.4. Conditions to avoid

Keep away from heat, sparks and flame.

#### 10.5. Incompatible materials

Acids. Glass. Strong bases. Strong oxidizing agents. Water.

#### 10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced. Hazardous decomposition products in case of fire, see Section 5.

#### **SECTION 11: Toxicological information**

#### 11.1. Information on toxicological effects

Acute toxicity (oral) : Toxic if swallowed.

Acute toxicity (dermal) : Toxic in contact with skin.

Acute toxicity (inhalation) : Toxic if inhaled.

Dimethylcarbamyl fluoride (431-14-1)	
ATE US (oral)	100 mg/kg body weight
ATE US (dermal)	300 mg/kg body weight
ATE US (gases)	700 ppmV/4h
ATE US (vapors)	3 mg/l/4h
ATE US (dust, mist)	0,5 mg/l/4h

Skin corrosion/irritation : Causes severe skin burns.
Serious eye damage/irritation : Causes serious eye damage.

Respiratory or skin sensitization : Not classified
Germ cell mutagenicity : Not classified
Carcinogenicity : Not classified
Reproductive toxicity : Not classified

STOT-single exposure : May cause respiratory irritation.

STOT-repeated exposure : Not classified

05.10.2023 (Issue date) EN (English US) 6/11

#### Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Aspiration hazard Viscosity, kinematic

Potential Adverse human health effects and

symptoms

Symptoms/effects

Symptoms/effects after inhalation

: Absorption of excessive F- can result in acute systemic fluorosis with hypocalcemia, interference with various metabolic functions and organ damage (heart, liver, kidneys).

The most important known symptoms and effects are described in the labelling (see section 2.2)

and/or in section 11.

: Not classified

: No data available

Material is destructive to tissue of the mucuous membranes and upper respiratory tract. Cough,

shortness of breath, headache, nausea.

#### **SECTION 12: Ecological information**

#### 12.1. Toxicity

No additional information available

#### 12.2. Persistence and degradability

No additional information available

#### 12.3. Bioaccumulative potential

No additional information available

#### 12.4. Mobility in soil

No additional information available

#### 12.5. Other adverse effects

No additional information available

#### **SECTION 13: Disposal considerations**

#### 13.1. Disposal methods

Waste treatment methods

Product/Packaging disposal recommendations

Additional information

Remove to an authorized incinerator equipped with an afterburner and a flue gas scrubber.

Dispose of contents/container in accordance with licensed collector's sorting instructions.

Recycle the material as far as possible.

#### **SECTION 14: Transport information**

#### 14.1. UN number

DOT NA No UN3286 UN-No. (TDG) UN3286 UN-No. (IMDG) 3286 UN-No. (IATA) 3286

#### 14.2. UN proper shipping name

Proper Shipping Name (DOT) : Flammable liquid, toxic, corrosive, n.o.s.

Proper Shipping Name (TDG) FLAMMABLE LIQUID, TOXIC, CORROSIVE, N.O.S. Proper Shipping Name (IMDG) FLAMMABLE LIQUID, TOXIC, CORROSIVE, N.O.S.

Proper Shipping Name (IATA) Flammable liquid, toxic, corrosive, n.o.s.

#### 14.3. Transport hazard class(es)

Transport hazard class(es) (DOT) : 3 (6.1, 8)

05.10.2023 (Issue date) EN (English US) 7/11

### Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Hazard labels (DOT) : 3, 6.1, 8



#### **TDG**

Transport hazard class(es) (TDG) : 3 (6.1) Hazard labels (TDG) : 3, 6.1



#### **IMDG**

Transport hazard class(es) (IMDG) : 3 (6.1, 8) Hazard labels (IMDG) : 3, 6.1, 8



#### IATA

Transport hazard class(es) (IATA) : 3 (6.1, 8) Hazard labels (IATA) : 3, 6.1, 8



#### 14.4. Packing group

Packing group (DOT) : II
Packing group (TDG) : II
Packing group (IMDG) : II
Packing group (IATA) : II

#### 14.5. Environmental hazards

Other information : No supplementary information available.

#### 14.6. Special precautions for user

#### DOT

UN-No.(DOT) : UN3286

05.10.2023 (Issue date) EN (English US) 8/11

#### Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

: 5 L

DOT Special Provisions (49 CFR 172.102)

: IB2 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite (31HZ1). Additional Requirement: Only liquids with a vapor pressure less than or equal to 110 kPa at 50 C (1.1 bar at 122 F), or 130 kPa at 55 C (1.3 bar at 131 F) are authorized. T11 - 6 178.274(d)(2) Normal................ 178.275(d)(3)

TP2 - a. The maximum degree of filling must not exceed the degree of filling determined by the following: (image) Where: tr is the maximum mean bulk temperature during transport, tf is the temperature in degrees celsius of the liquid during filling, and a is the mean coefficient of cubical expansion of the liquid between the mean temperature of the liquid during filling (tf) and the maximum mean bulk temperature during transportation (tr) both in degrees celsius. b. For liquids transported under ambient conditions may be calculated using the formula: (image) Where: d15 and d50 are the densities (in units of mass per unit volume) of the liquid at 15 C (59 F) and 50 C (122 F), respectively.

TP13 - Self-contained breathing apparatus must be provided when this hazardous material is transported by sea.

TP27 - A portable tank having a minimum test pressure of 4 bar (400 kPa) may be used provided the calculated test pressure is 4 bar or less based on the MAWP of the hazardous material, as defined in 178.275 of this subchapter, where the test pressure is 1.5 times the MAWP.

DOT Packaging Exceptions (49 CFR 173.xxx) : 150
DOT Packaging Non Bulk (49 CFR 173.xxx) : 202
DOT Packaging Bulk (49 CFR 173.xxx) : 243
DOT Quantity Limitations Passenger aircraft/rail (49 : 1 L

CFR 173.27)

DOT Quantity Limitations Cargo aircraft only (49

CFR 175.75)

**DOT Vessel Stowage Location** 

: B - (i) The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel carrying a number of passengers limited to not more than the larger of 25 passengers, or one passenger per each 3 m of overall vessel length; and (ii) "On deck only" on passenger vessels in which the number of passengers specified in paragraph (k)(2)(i) of this section is exceeded.

DOT Vessel Stowage Other

21 - Segregation same as for flammable liquids,40 - Stow "clear of living quarters",100 - Stow "away from" flammable solids

**TDG** 

UN-No. (TDG) : UN3286

TDG Special Provisions

: 16 - 1) The technical name of the most dangerous substance related to the primary class must be shown, in parentheses, on the shipping document following the shipping name in accordance with clause 3.5(1)(c)(i)(A) of Part 3, Documentation. The technical name must also be shown, in parentheses, on a small means of containment or on a tag following the shipping name in accordance with subsections 4.11(2) and (3) of Part 4, Dangerous Goods Safety Marks.

2) subsection (1), the technical name for the following dangerous goods is not required to be shown on a shipping document or on a small means of containment when Canadian law for domestic transport or an international convention for international transport prohibits the disclosure of the technical: a) UN1544, ALKALOID SALTS, SOLID, N.O.S. or ALKALOIDS, SOLID, N.O.S; b) UN1851, MEDICINE, LIQUID, TOXIC, N.O.S; c) UN3140, ALKALOID SALTS, LIQUID, N.O.S. or ALKALOIDS, LIQUID, N.O.S; d) UN3248, MEDICINE, LIQUID, FLAMMABLE, TOXIC, N.O.S; or e) UN3249, MEDICINE, SOLID, TOXIC, N.O.S. An example in Canada is the "Food and Drugs Act".

Explosive Limit and Limited Quantity Index : 1 L
Excepted quantities (TDG) : E2
Passenger Carrying Road Vehicle or Passenger : 1 L
Carrying Railway Vehicle Index

Emergency Response Guide (ERG) Number : 131

**IMDG** 

Special provision (IMDG): 274Limited quantities (IMDG): 1 LExcepted quantities (IMDG): E2Packing instructions (IMDG): P001

05.10.2023 (Issue date) EN (English US) 9/11

#### Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

IBC packing instructions (IMDG) : IBC99
Tank instructions (IMDG) : T11

Tank special provisions (IMDG) : TP2, TP13, TP27

EmS-No. (Fire) : F-E - FIRE SCHEDULE Echo - NON-WATER-REACTIVE FLAMMABLE LIQUIDS EmS-No. (Spillage) : S-C - SPILLAGE SCHEDULE Charlie - FLAMMABLE CORROSIVE LIQUIDS

Stowage category (IMDG) : B
Stowage and handling (IMDG) : SW2
Segregation (IMDG) : SG5, SG8

Properties and observations (IMDG) : Flammable, toxic, corrosive liquid. Toxic if swallowed, by skin contact or by inhalation. Causes

burns to skin, eyes and mucous membranes.

#### IATA

PCA Excepted quantities (IATA) : E2 : Y340 PCA Limited quantities (IATA) PCA limited quantity max net quantity (IATA) : 0.5L : 352 PCA packing instructions (IATA) PCA max net quantity (IATA) : 1L CAO packing instructions (IATA) : 363 CAO max net quantity (IATA) : 5L ERG code (IATA) : 3CP

#### 14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

#### **SECTION 15: Regulatory information**

#### 15.1. US Federal regulations

All components of this product are present and listed as Active on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory, except for:

Dimethylcarbamyl fluoride CAS-No. 431-14-1 100%

#### 15.2. International regulations

#### **CANADA**

No additional information available

#### **EU-Regulations**

No additional information available

#### **National regulations**

No additional information available

#### 15.3. US State regulations

California Proposition 65 - This product does not contain any substances known to the state of California to cause cancer, developmental and/or reproductive harm

#### **SECTION 16: Other information**

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Full text of H-phrases		
H226	Flammable liquid and vapor	
H301	Toxic if swallowed	

#### Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Full text of H-phrases		
H311	Toxic in contact with skin	
H314	Causes severe skin burns and eye damage	
H318	Causes serious eye damage	
H331	Toxic if inhaled	
H335	May cause respiratory irritation	

NFPA health hazard

: 3 - Materials that, under emergency conditions, can cause serious or permanent injury.

NFPA fire hazard

 2 - Materials that must be moderately heated or exposed to relatively high ambient temperatures before ignition can occur.

NFPA reactivity

: 1 - Materials that in themselves are normally stable but can become unstable at elevated temperatures and pressures.



Hazard Rating

Health

Flammability

Physical

Safety Data Sheet (SDS), USA

: 3 Serious Hazard - Major injury likely unless prompt action is taken and medical treatment is

: 2 Moderate Hazard - Materials which must be moderately heated or exposed to high ambient temperatures before ignition will occur. Includes liquids having a flash point at or above 100 F but below 200 F. (Classes II IIIA)

: 1 Slight Hazard - Materials that are normally stable but can become unstable (self-react) at high temperatures and pressures. Materials may react non-violently with water or undergo hazardous polymerization in the absence of inhibitors.