

1,1,2,2-Tetrafluoroethyl 2,2,3,3-tetrafluoropropyl ether, battery grade

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations
SDS ID: 2107356
Issue date: 11/23/2015 Revision date: 3/26/2025 Version: 1.1

SECTION 1: Identification

1.1. Identification

Product form	: Substance
Substance name	: 1,1,2,2-Tetrafluoroethyl 2,2,3,3-tetrafluoropropyl ether, battery grade
CAS-No.	: 16627-68-2
Product code	: 6164-3-24
Formula	: C ₅ H ₄ F ₈ O
Synonyms	: 1,1,2,2-Tetrafluoro-3-(1,1,2,2-tetrafluoroethoxy)propane
Other means of identification	: MFCD00155961

1.2. Recommended use and restrictions on use

Use of the substance/mixture	: Laboratory chemicals Manufacture of substances Scientific research and development
------------------------------	--

1.3. Supplier

SynQuest Laboratories, Inc.
P.O. Box 309
Alachua, FL, Alachua, 32615
United States of America
T (386) 462-0788 - F (386) 462-7097
info@synquestlabs.com - www.synquestlabs.com

1.4. Emergency telephone number

Emergency number	: (844) 523-4086 (3E Company - Account 10069)
------------------	---

SECTION 2: Hazard(s) identification

2.1. Classification of the substance or mixture

GHS US classification

Flammable liquids Category 3	H226	Flammable liquid and vapor
Skin corrosion/irritation Category 2	H315	Causes skin irritation
Serious eye damage/eye irritation Category 2A	H319	Causes serious eye irritation
Specific target organ toxicity – Single exposure, Category 3, Narcosis	H336	May cause drowsiness or dizziness
Specific target organ toxicity – Single exposure, Category 3, Respiratory tract irritation	H335	May cause respiratory irritation
Full text of H statements : see section 16		

2.2. GHS Label elements, including precautionary statements

GHS US labeling

Hazard pictograms (GHS US)	:	 
Signal word (GHS US)	:	Warning
Hazard statements (GHS US)	:	H226 - Flammable liquid and vapor H315 - Causes skin irritation

1,1,2,2-Tetrafluoroethyl 2,2,3,3-tetrafluoropropyl ether, battery grade

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Precautionary statements (GHS US)	H319 - Causes serious eye irritation H335 - May cause respiratory irritation H336 - May cause drowsiness or dizziness
	: P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P233 - Keep container tightly closed. P240 - Ground/Bond container and receiving equipment. P241 - Use explosion-proof electrical/ventilating/lighting equipment P242 - Use only non-sparking tools. P243 - Take precautionary measures against static discharge. P261 - Avoid breathing fumes, mist, spray, vapors. P264 - Wash skin thoroughly after handling P271 - Use only outdoors or in a well-ventilated area. P280 - Wear protective gloves/protective clothing/eye protection/face protection. P302+P352 - If on skin: Wash with plenty of soap and water P303+P361+P353 - If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. P304+P340 - If inhaled: Remove person to fresh air and keep comfortable for breathing. P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P312 - Call a POISON CENTER or doctor/physician if you feel unwell P321 - Specific treatment (see supplemental first aid instructions on this label) P332+P313 - If skin irritation occurs: Get medical advice/attention. P337+P313 - If eye irritation persists: Get medical advice/attention. P362+P364 - Take off contaminated clothing and wash it before reuse. P370+P378 - In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish P403+P233 - Store in a well-ventilated place. Keep container tightly closed. P403+P235 - Store in a well-ventilated place. Keep cool. P405 - Store locked up. P501 - Dispose of contents/container to an approved waste disposal plant

2.3. Other hazards which do not result in classification

No additional information available

2.4. Unknown acute toxicity (GHS US)

No additional information available

SECTION 3: Composition/Information on ingredients

3.1. Substances

Substance type : Mono-constituent

Name	Product identifier	%	GHS US classification
1,1,2,2-Tetrafluoroethyl 2,2,3,3-tetrafluoropropyl ether, battery grade (Main constituent)	CAS-No.: 16627-68-2	≤ 100	Flam. Liq. 3, H226 Skin Irrit. 2, H315 Eye Irrit. 2A, H319 STOT SE 3, H336 STOT SE 3, H335

Full text of hazard classes and H-statements : see section 16

3.2. Mixtures

Not applicable

1,1,2,2-Tetrafluoroethyl 2,2,3,3-tetrafluoropropyl ether, battery grade

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 4: First-aid measures

4.1. Description of first aid measures

First-aid measures general	: In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible). Move the affected personnel away from the contaminated area.
First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing. If not breathing, give artificial respiration. Get medical advice/attention.
First-aid measures after skin contact	: Wash with plenty of soap and water. Get medical advice/attention.
First-aid measures after eye contact	: Immediately flush eyes thoroughly with water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical advice/attention.
First-aid measures after ingestion	: Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Rinse mouth out with water. Get medical advice/attention.

4.2. Most important symptoms and effects (acute and delayed)

Symptoms/effects	: The most important known symptoms and effects are described in the labelling (see section 2.2) and/or in section 11.
Symptoms/effects after inhalation	: May cause drowsiness or dizziness.

4.3. Immediate medical attention and special treatment, if necessary

Treat symptomatically.

SECTION 5: Fire-fighting measures

5.1. Suitable (and unsuitable) extinguishing media

Suitable extinguishing media	: Alcohol resistant foam. Carbon dioxide. Dry powder. Water spray. Use extinguishing media appropriate for surrounding fire.
------------------------------	--

5.2. Specific hazards arising from the chemical

Fire hazard	: Thermal decomposition generates: Carbon oxides. Hydrogen fluoride.
Explosion hazard	: Risk of explosion if heated under confinement. Use water spray or fog for cooling exposed containers. May form flammable/explosive vapor-air mixture.

5.3. Special protective equipment and precautions for fire-fighters

Firefighting instructions	: In case of fire: Evacuate area. Fight fire remotely due to the risk of explosion.
Protection during firefighting	: Wear gas tight chemically protective clothing in combination with self contained breathing apparatus. For further information refer to section 8: "Exposure controls/personal protection".

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures	: Evacuate unnecessary personnel. Ensure adequate air ventilation. Do not breathe gas, fumes, vapor or spray.
------------------	---

6.1.1. For non-emergency personnel

Emergency procedures	: Only qualified personnel equipped with suitable protective equipment may intervene.
----------------------	---

6.1.2. For emergency responders

Protective equipment	: Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".
Emergency procedures	: Gas/vapor heavier than air. May accumulate in confined spaces, particularly at or below ground level. Consider the risk of potentially explosive atmospheres. Eliminate every possible source of ignition.

1,1,2,2-Tetrafluoroethyl 2,2,3,3-tetrafluoropropyl ether, battery grade

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

6.2. Environmental precautions

Avoid release to the environment. Notify authorities if product enters sewers or public waters.

6.3. Methods and material for containment and cleaning up

- | | | |
|-------------------------|---|---|
| For containment | : | Stop leak if safe to do so. Dike for recovery or absorb with appropriate material. |
| Methods for cleaning up | : | Take up large spills with pump or vacuum and finish with dry chemical absorbent. Use explosion-proof equipment. Take up small spills with dry chemical absorbent. Sweep or shovel spills into appropriate container for disposal. Ventilate area. |
| Other information | : | For disposal of solid materials or residues refer to section 13 : "Disposal considerations". |

6.4. Reference to other sections

No additional information available

SECTION 7: Handling and storage

7.1. Precautions for safe handling

- | | | |
|-----------------------------------|---|---|
| Additional hazards when processed | : | Handle empty containers with care because residual vapors are flammable. |
| Precautions for safe handling | : | Do not handle until all safety precautions have been read and understood. Ensure good ventilation of the work station. Do not breathe fumes, mist, spray, vapors. Wear personal protective equipment. Avoid contact with skin and eyes. Keep away from ignition sources (including static discharges). Proper grounding procedures to avoid static electricity should be followed. Use only non-sparking tools. |
| Hygiene measures | : | Handle in accordance with good industrial hygiene and safety procedures. Do not eat, drink or smoke when using this product. Always wash hands after handling the product. |

7.2. Conditions for safe storage, including any incompatibilities

- | | | |
|------------------------|---|---|
| Technical measures | : | Comply with applicable regulations. |
| Storage conditions | : | Keep container closed when not in use. Keep away from ignition sources. |
| Incompatible materials | : | Refer to Section 10 on Incompatible Materials. |
| Storage area | : | Store in dry, cool, well-ventilated area. |

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

No additional information available

8.2. Appropriate engineering controls

- | | | |
|----------------------------------|---|---|
| Appropriate engineering controls | : | Ensure good ventilation of the work station. Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure. |
|----------------------------------|---|---|

8.3. Individual protection measures/Personal protective equipment

Hand protection:
protective gloves. 29 CFR 1910.138: Hand Protection
Eye protection:
Chemical goggles or safety glasses. Face shield. 29 CFR 1910.133: Eye and Face Protection
Skin and body protection:
Wear suitable protective clothing

1,1,2,2-Tetrafluoroethyl 2,2,3,3-tetrafluoropropyl ether, battery grade

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Respiratory protection:

In case of inadequate ventilation wear respiratory protection. 29 CFR 1910.134: Respiratory Protection

Personal protective equipment symbol(s):



Other information:

Safety shoes. 29 CFR 1910.136: Foot Protection.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Color	: No data available
Odor	: No data available
Odor threshold	: No data available
pH	: No data available
Melting point	: No data available
Freezing point	: No data available
Boiling point	: 93.2 °C
Flash point	: 27.5 °C
Relative evaporation rate (butyl acetate=1)	: No data available
Flammability (solid, gas)	: No data available
Vapor pressure	: No data available
Relative vapor density at 20 °C	: No data available
Relative density	: No data available
Density	: 1.5323 g/ml (@ 20 °C)
Molecular mass	: 232.07 g/mol
Solubility	: No data available
Partition coefficient n-octanol/water (Log Pow)	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosion limits	: No data available
Explosive properties	: No data available
Oxidizing properties	: No data available

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

No additional information available

10.2. Chemical stability

The product is stable at normal handling and storage conditions.

1,1,2,2-Tetrafluoroethyl 2,2,3,3-tetrafluoropropyl ether, battery grade

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

10.3. Possibility of hazardous reactions

No additional information available

10.4. Conditions to avoid

No additional information available

10.5. Incompatible materials

Strong oxidizing agents.

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced. Hazardous decomposition products in case of fire, see Section 5.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral)	: Not classified
Acute toxicity (dermal)	: Not classified
Acute toxicity (inhalation)	: Not classified
Skin corrosion/irritation	: Causes skin irritation.
Serious eye damage/irritation	: Causes serious eye irritation.
Respiratory or skin sensitization	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified
Reproductive toxicity	: Not classified
STOT-single exposure	: May cause drowsiness or dizziness. May cause respiratory irritation.
STOT-repeated exposure	: Not classified
Aspiration hazard	: Not classified
Viscosity, kinematic	: No data available
Symptoms/effects	: The most important known symptoms and effects are described in the labelling (see section 2.2) and/or in section 11.
Symptoms/effects after inhalation	: May cause drowsiness or dizziness.

SECTION 12: Ecological information

12.1. Toxicity

No additional information available

12.2. Persistence and degradability

1,1,2,2-Tetrafluoroethyl 2,2,3,3-tetrafluoropropyl ether, battery grade (16627-68-2)

Persistence and degradability	Rapidly degradable
-------------------------------	--------------------

12.3. Bioaccumulative potential

No additional information available

12.4. Mobility in soil

No additional information available

1,1,2,2-Tetrafluoroethyl 2,2,3,3-tetrafluoropropyl ether, battery grade

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

12.5. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1. Disposal methods

Waste treatment methods	: Remove to an authorized incinerator equipped with an afterburner and a flue gas scrubber.
Product/Packaging disposal recommendations	: Dispose of contents/container in accordance with licensed collector's sorting instructions.
Additional information	: Recycle the material as far as possible.

SECTION 14: Transport information

14.1. UN number

DOT NA No	: UN3271
UN-No. (TDG)	: UN3271
UN-No. (IMDG)	: 3271
UN-No. (IATA)	: 3271

14.2. UN proper shipping name

Proper Shipping Name (DOT)	: Ethers, n.o.s.
Proper Shipping Name (TDG)	: ETHERS, N.O.S.
Proper Shipping Name (IMDG)	: ETHERS, N.O.S.
Proper Shipping Name (IATA)	: Ethers, n.o.s.

14.3. Transport hazard class(es)

DOT

Transport hazard class(es) (DOT)	: 3
Hazard labels (DOT)	: 3



TDG

Transport hazard class(es) (TDG)	: 3
Hazard labels (TDG)	: 3



IMDG

Transport hazard class(es) (IMDG)	: 3
Hazard labels (IMDG)	: 3



IATA

Transport hazard class(es) (IATA)	: 3
Hazard labels (IATA)	: 3

1,1,2,2-Tetrafluoroethyl 2,2,3,3-tetrafluoropropyl ether, battery grade

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations



14.4. Packing group

Packing group (DOT)	: III
Packing group (TDG)	: III
Packing group (IMDG)	: III
Packing group (IATA)	: III

14.5. Environmental hazards

Other information	: No supplementary information available.
-------------------	---

14.6. Special precautions for user

DOT

UN-No.(DOT)	: UN3271
DOT Special Provisions (49 CFR 172.102)	: B1 - If the material has a flash point at or above 38 C (100 F) and below 93 C (200 F), then the bulk packaging requirements of 173.241 of this subchapter are applicable. If the material has a flash point of less than 38 C (100 F), then the bulk packaging requirements of 173.242 of this subchapter are applicable. IB3 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite (31HZ1 and 31HA2, 31HB2, 31HN2, 31HD2 and 31HH2). Additional Requirement: Only liquids with a vapor pressure less than or equal to 110 kPa at 50 C (1.1 bar at 122 F), or 130 kPa at 55 C (1.3 bar at 131 F) are authorized, except for UN2672 (also see Special Provision IP8 in Table 2 for UN2672). T4 - 2.65 178.274(d)(2) Normal..... 178.275(d)(3) TP1 - The maximum degree of filling must not exceed the degree of filling determined by the following: Degree of filling = $97 / 1 + a (tr - tf)$ Where: tr is the maximum mean bulk temperature during transport, and tf is the temperature in degrees celsius of the liquid during filling. TP29 - A portable tank having a minimum test pressure of 1.5 bar (150.0 kPa) may be used provided the calculated test pressure is 1.5 bar or less based on the MAWP of the hazardous materials, as defined in 178.275 of this subchapter, where the test pressure is 1.5 times the MAWP.
DOT Packaging Exceptions (49 CFR 173.xxx)	: 150
DOT Packaging Non Bulk (49 CFR 173.xxx)	: 203
DOT Packaging Bulk (49 CFR 173.xxx)	: 242
DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27)	: 60 L
DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75)	: 220 L
DOT Vessel Stowage Location	: A - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel.

TDG

UN-No. (TDG)	: UN3271
--------------	----------

1,1,2,2-Tetrafluoroethyl 2,2,3,3-tetrafluoropropyl ether, battery grade

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

TDG Special Provisions	: 16 - 1) The technical name of the most dangerous substance related to the primary class must be shown, in parentheses, on the shipping document following the shipping name in accordance with clause 3.5(1)(c)(i)(A) of Part 3, Documentation. The technical name must also be shown, in parentheses, on a small means of containment or on a tag following the shipping name in accordance with subsections 4.11(2) and (3) of Part 4, Dangerous Goods Safety Marks. 2) subsection (1), the technical name for the following dangerous goods is not required to be shown on a shipping document or on a small means of containment when Canadian law for domestic transport or an international convention for international transport prohibits the disclosure of the technical: a) UN1544, ALKALOID SALTS, SOLID, N.O.S. or ALKALOIDS, SOLID, N.O.S; b) UN1851, MEDICINE, LIQUID, TOXIC, N.O.S; c) UN3140, ALKALOID SALTS, LIQUID, N.O.S. or ALKALOIDS, LIQUID, N.O.S; d) UN3248, MEDICINE, LIQUID, FLAMMABLE, TOXIC, N.O.S; or e) UN3249, MEDICINE, SOLID, TOXIC, N.O.S. An example in Canada is the "Food and Drugs Act".
Explosive Limit and Limited Quantity Index	: 5 L
Excepted quantities (TDG)	: E1
Passenger Carrying Road Vehicle or Passenger Carrying Railway Vehicle Index	: 60 L
Emergency Response Guide (ERG) Number	: 127
IMDG	
Special provision (IMDG)	: 223, 274
Limited quantities (IMDG)	: 5 L
Excepted quantities (IMDG)	: E1
Packing instructions (IMDG)	: P001, LP01
IBC packing instructions (IMDG)	: IBC03
Tank instructions (IMDG)	: T4
Tank special provisions (IMDG)	: TP1, TP29
EmS-No. (Fire)	: F-E - FIRE SCHEDULE Echo - NON-WATER-REACTIVE FLAMMABLE LIQUIDS
EmS-No. (Spillage)	: S-D - SPILLAGE SCHEDULE Delta - FLAMMABLE LIQUIDS
Stowage category (IMDG)	: A

IATA

PCA Excepted quantities (IATA)	: E1
PCA Limited quantities (IATA)	: Y344
PCA limited quantity max net quantity (IATA)	: 10L
PCA packing instructions (IATA)	: 355
PCA max net quantity (IATA)	: 60L
CAO packing instructions (IATA)	: 366
CAO max net quantity (IATA)	: 220L
Special provision (IATA)	: A3
ERG code (IATA)	: 3L

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1. US Federal regulations

All components of this product are present and listed as Active on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory, except for:

1,1,2,2-Tetrafluoroethyl 2,2,3,3-tetrafluoropropyl ether, battery grade	CAS-No. 16627-68-2	100%
---	--------------------	------

1,1,2,2-Tetrafluoroethyl 2,2,3,3-tetrafluoropropyl ether, battery grade

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

15.2. International regulations

CANADA

No additional information available

EU-Regulations

No additional information available

National regulations

1,1,2,2-Tetrafluoroethyl 2,2,3,3-tetrafluoropropyl ether, battery grade (16627-68-2)

Listed on KECL/KECI (Korean Existing Chemicals Inventory)

Listed on the TCSI (Taiwan Chemical Substance Inventory)

Listed on the NCI (Vietnam - National Chemical Inventory)

15.3. US State regulations

California Proposition 65 - This product does not contain any substances known to the state of California to cause cancer, developmental and/or reproductive harm

SECTION 16: Other information

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Revision date : 3/26/2025

Full text of H-phrases	
H226	Flammable liquid and vapor
H315	Causes skin irritation
H319	Causes serious eye irritation
H335	May cause respiratory irritation
H336	May cause drowsiness or dizziness

NFPA health hazard


: 2 - Materials that, under emergency conditions, can cause temporary incapacitation or residual injury.

NFPA fire hazard

: 3 - Liquids and solids (including finely divided suspended solids) that can be ignited under almost all ambient temperature conditions.

NFPA reactivity

: 0 - Material that in themselves are normally stable, even under fire conditions.



Hazard Rating

Health

: 1 Slight Hazard - Irritation or minor reversible injury possible

Flammability

: 3 Serious Hazard - Materials capable of ignition under almost all normal temperature conditions. Includes flammable liquids with flash points below 73 F and boiling points above 100 F. as well as liquids with flash points between 73 F and 100 F. (Classes IB IC)

Physical

: 0 Minimal Hazard - Materials that are normally stable, even under fire conditions, and will NOT react with water, polymerize, decompose, condense, or self-react. Non-Explosives.

Safety Data Sheet (SDS), USA

The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. The information in this document is based on the present state of our knowledge and is offered solely for your consideration, investigation, and verification. It does not represent any guarantee of the properties of the product nor that the hazard precautions or procedures described are the only ones which exist. SynQuest shall not be held liable or any damage resulting from handling or from contact with the above product.