

# Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations SDS ID: 6H64114

Issue date: 12/13/2022 Version: 1.0

## **SECTION 1: Identification**

#### 1.1. Identification

Product form : Substance
Substance name : Ethylene sulfate
CAS-No. : 1072-53-3
Product code : 6H64-1-14
Formula : C2H4O4S

Synonyms : 1,3,2-Dioxathiolan-2,2-dioxide

Other means of identification : MFCD00221769

#### 1.2. Recommended use and restrictions on use

Use of the substance/mixture : Laboratory chemicals

Manufacture of substances

Scientific research and development

### 1.3. Supplier

SynQuest Laboratories, Inc. Inc.

P.O. Box 309

Alachua, FL, Alachua, 32615 United States of America

T (386) 462-0788 - F (386) 462-7097

info@synquestlabs.com - www.synquestlabs.com

## 1.4. Emergency telephone number

Emergency number : (844) 523-4086 (3E Company - Account 10069)

# SECTION 2: Hazard(s) identification

#### 2.1. Classification of the substance or mixture

#### **GHS US classification**

Acute toxicity (oral) Category 4 H302 Harmful if swallowed

Skin corrosion/irritation Category 1B H314 Causes severe skin burns and eye damage

Serious eye damage/eye irritation Category 1 H318 Causes serious eye damage Specific target organ toxicity – Single exposure, Category 3, H335 May cause respiratory irritation

Respiratory tract irritation

Full text of H statements : see section 16

## 2.2. GHS Label elements, including precautionary statements

### **GHS US labeling**

Hazard pictograms (GHS US)





Signal word (GHS US) : Danger

Hazard statements (GHS US) : H302 - Harmful if swallowed

H314 - Causes severe skin burns and eye damage

H318 - Causes serious eye damage H335 - May cause respiratory irritation

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Precautionary statements (GHS US)

: P260 - Do not breathe dust, mist, spray.

P264 - Wash skin thoroughly after handling

P270 - Do not eat, drink or smoke when using this product.

P271 - Use only outdoors or in a well-ventilated area.

P280 - Wear protective gloves/protective clothing/eye protection/face protection.

P301+P312 - If swallowed: Call a POISON CENTER or doctor/ physician if you feel unwell

P301+P330+P331 - If swallowed: rinse mouth. Do NOT induce vomiting.

P303+P361+P353 - If on skin (or hair): Take off immediately all contaminated clothing. Rinse

skin with water/shower.

P304+P340 - If inhaled: Remove person to fresh air and keep comfortable for breathing. P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove

contact lenses, if present and easy to do. Continue rinsing. P310 - Immediately call a POISON CENTER or doctor/ physician

P321 - Specific treatment (see supplemental first aid instructions on this label)

P330 - Rinse mouth.

P363 - Wash contaminated clothing before reuse.

P403+P233 - Store in a well-ventilated place. Keep container tightly closed.

P405 - Store locked up.

P501 - Dispose of contents/container to an approved waste disposal plant

### 2.3. Other hazards which do not result in classification

No additional information available

### 2.4. Unknown acute toxicity (GHS US)

Not applicable

## **SECTION 3: Composition/Information on ingredients**

## 3.1. Substances

Substance type : Mono-constituent

| Name                                | Product identifier | % | GHS US classification   |
|-------------------------------------|--------------------|---|---|
| Ethylene sulfate (Main constituent) | CAS-No.: 1072-53-3 |   | Acute Tox. 4 (Oral), H302<br>Skin Corr. 1B, H314<br>Eye Dam. 1, H318<br>STOT SE 3, H335 |

Full text of hazard classes and H-statements : see section 16

#### 3.2. Mixtures

Not applicable

## **SECTION 4: First-aid measures**

## 4.1. Description of first aid measures

First-aid measures general

: In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible). Move the affected personnel away from the contaminated area.

First-aid measures after inhalation

: Remove person to fresh air and keep comfortable for breathing. If not breathing, give artificial respiration. Get immediate medical advice/attention.

First-aid measures after skin contact

: Wash with plenty of soap and water. Remove contaminated clothing and shoes. Get immediate medical advice/attention.

First-aid measures after eye contact

: Immediately flush eyes thoroughly with water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get immediate medical advice/attention.

12/13/2022 (Issue date) EN (English US) 2/10

# Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

First-aid measures after ingestion

: Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Rinse mouth out with water. Get immediate medical advice/attention.

### 4.2. Most important symptoms and effects (acute and delayed)

Symptoms/effects

: The most important known symptoms and effects are described in the labelling (see section 2.2) and/or in section 11.

Symptoms/effects after inhalation

: Material is destructive to tissue of the mucuous membranes and upper respiratory tract. Cough, shortness of breath, headache, nausea.

### 4.3. Immediate medical attention and special treatment, if necessary

Treat symptomatically.

## **SECTION 5: Fire-fighting measures**

#### 5.1. Suitable (and unsuitable) extinguishing media

Suitable extinguishing media

: Alcohol resistant foam. Carbon dioxide. Dry powder. Water spray. Use extinguishing media appropriate for surrounding fire.

#### 5.2. Specific hazards arising from the chemical

Fire hazard

: Thermal decomposition generates: Carbon oxides. Sulfur oxides.

Explosion hazard

: Risk of explosion if heated under confinement. Use water spray or fog for cooling exposed

containers. May form flammable/explosive vapor-air mixture.

Hazardous decomposition products in case of fire,

see Section 5

: Toxic fumes may be released.

#### 5.3. Special protective equipment and precautions for fire-fighters

Firefighting instructions

: In case of fire: Evacuate area. Fight fire remotely due to the risk of explosion.

Protection during firefighting

: Wear gas tight chemically protective clothing in combination with self contained breathing apparatus. For further information refer to section 8: "Exposure controls/personal protection".

### **SECTION 6: Accidental release measures**

### 6.1. Personal precautions, protective equipment and emergency procedures

General measures

: Evacuate unnecessary personnel. Ensure adequate air ventilation. Do not breathe dust.

6.1.1. For non-emergency personnel

Emergency procedures

: Only qualified personnel equipped with suitable protective equipment may intervene.

6.1.2. For emergency responders

Protective equipment

: Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".

**Emergency procedures** 

: Prevent from entering sewers, basements and workpits, or any place where its accumulation can be dangerous.

bo dangon

## 6.2. Environmental precautions

Avoid release to the environment. Notify authorities if product enters sewers or public waters.

## 6.3. Methods and material for containment and cleaning up

For containment

: Stop leak if safe to do so.

Methods for cleaning up

: Sweep or shovel spills into appropriate container for disposal. Minimize generation of dust.

Other information

: For disposal of solid materials or residues refer to section 13 : "Disposal considerations".

12/13/2022 (Issue date) EN (English US) 3/10

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

## 6.4. Reference to other sections

No additional information available

# **SECTION 7: Handling and storage**

### 7.1. Precautions for safe handling

Precautions for safe handling : Do not handle until all safety precautions have been read and understood. Ensure good

ventilation of the work station. Do not breathe dust, mist, spray. Wear personal protective

equipment. Avoid contact with skin and eyes.

Hygiene measures : Handle in accordance with good industrial hygiene and safety procedures. Do not eat, drink or

smoke when using this product. Always wash hands after handling the product.

### 7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Comply with applicable regulations.
Storage conditions : Keep container closed when not in use.
Incompatible materials : Refer to Section 10 on Incompatible Materials.

Storage temperature : 2-8 °C

Storage area : Store in dry, well-ventilated area.

## **SECTION 8: Exposure controls/personal protection**

## 8.1. Control parameters

### Ethylene sulfate (1072-53-3)

No additional information available

## 8.2. Appropriate engineering controls

Appropriate engineering controls

: Ensure good ventilation of the work station. Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure.

## 8.3. Individual protection measures/Personal protective equipment

#### Hand protection:

protective gloves. 29 CFR 1910.138: Hand Protection

#### Eye protection:

Chemical goggles or safety glasses. Face shield. 29 CFR 1910.133: Eye and Face Protection

## Skin and body protection:

Wear suitable protective clothing

### Respiratory protection:

In case of inadequate ventilation wear respiratory protection. 29 CFR 1910.134: Respiratory Protection

#### Personal protective equipment symbol(s):









12/13/2022 (Issue date) EN (English US) 4/10

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

#### Other information:

Safety shoes. 29 CFR 1910.136: Foot Protection.

## **SECTION 9: Physical and chemical properties**

# 9.1. Information on basic physical and chemical properties

Physical state : Solid

Color : No data available
Odor : No data available
Odor threshold : No data available
pH : No data available
Melting point : 97 – 99 °C
Freezing point : No data available

Boiling point : No data available Flash point : No data available Relative evaporation rate (butyl acetate=1) : No data available Flammability (solid, gas) : No data available : No data available Vapor pressure Relative vapor density at 20 °C : No data available Relative density : No data available Molecular mass : 124.116 g/mol : No data available Solubility Partition coefficient n-octanol/water (Log Pow) : No data available Auto-ignition temperature : No data available Decomposition temperature : No data available Viscosity, kinematic : No data available Viscosity, dynamic : No data available **Explosion limits** No data available Explosive properties : No data available Oxidizing properties : No data available

## 9.2. Other information

No additional information available

# **SECTION 10: Stability and reactivity**

## 10.1. Reactivity

No additional information available

## 10.2. Chemical stability

The product is stable at normal handling and storage conditions.

#### 10.3. Possibility of hazardous reactions

Reacts violently with (strong) oxidizers.

### 10.4. Conditions to avoid

Keep away from heat, sparks and flame.

# 10.5. Incompatible materials

Strong oxidizing agents.

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### 10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced. Hazardous decomposition products in case of fire, see Section 5.

## **SECTION 11: Toxicological information**

## 11.1. Information on toxicological effects

Acute toxicity (oral) : Harmful if swallowed.
Acute toxicity (dermal) : Not classified
Acute toxicity (inhalation) : Not classified

Skin corrosion/irritation : Causes severe skin burns.
Serious eye damage/irritation : Causes serious eye damage.

Respiratory or skin sensitization : Not classified
Germ cell mutagenicity : Not classified
Carcinogenicity : Not classified
Reproductive toxicity : Not classified

STOT-single exposure : May cause respiratory irritation.

STOT-repeated exposure : Not classified
Aspiration hazard : Not classified
Viscosity, kinematic : No data available

Symptoms/effects : The most important known symptoms and effects are described in the labelling (see section 2.2)

and/or in section 11.

Symptoms/effects after inhalation : Material is destructive to tissue of the mucuous membranes and upper respiratory tract. Cough,

shortness of breath, headache, nausea.

# **SECTION 12: Ecological information**

### 12.1. Toxicity

No additional information available

## 12.2. Persistence and degradability

No additional information available

## 12.3. Bioaccumulative potential

No additional information available

## 12.4. Mobility in soil

No additional information available

#### 12.5. Other adverse effects

No additional information available

## **SECTION 13: Disposal considerations**

# 13.1. Disposal methods

Waste treatment methods

Product/Packaging disposal recommendations

Additional information

- : Remove to an authorized incinerator equipped with an afterburner and a flue gas scrubber.
- : Dispose of contents/container in accordance with licensed collector's sorting instructions.
- : Recycle the material as far as possible.

12/13/2022 (Issue date) EN (English US) 6/10

# Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

## **SECTION 14: Transport information**

## **14.1. UN number**

DOT NA No : UN3261 UN-No. (TDG) : Not applicable UN-No. (IMDG) : 3261 UN-No. (IATA) : 3261

## 14.2. UN proper shipping name

Proper Shipping Name (DOT) : Corrosive solid, acidic, organic, n.o.s.

Proper Shipping Name (TDG) : Not applicable

Proper Shipping Name (IMDG) : CORROSIVE SOLID, ACIDIC, ORGANIC, N.O.S.

Proper Shipping Name (IATA) : Corrosive solid, acidic, organic, n.o.s.

# 14.3. Transport hazard class(es)

#### DOT

Transport hazard class(es) (DOT) : 8
Hazard labels (DOT) : 8



#### **TDG**

Transport hazard class(es) (TDG) : Not applicable

#### **IMDG**

Transport hazard class(es) (IMDG) : 8
Hazard labels (IMDG) : 8



## IATA

Transport hazard class(es) (IATA) : 8
Hazard labels (IATA) : 8



## 14.4. Packing group

Packing group (DOT) : II

Packing group (TDG) : Not applicable

Packing group (IMDG) : II
Packing group (IATA) : II

# 14.5. Environmental hazards

Other information : No supplementary information available.

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### 14.6. Special precautions for user

DOT

UN-No.(DOT)

DOT Special Provisions (49 CFR 172.102) IB8 - Authorized IBCs: Metal (11A, 11B, 11N, 21A, 21B, 21N, 31A, 31B and 31N); Rigid plastics

(11H1, 11H2, 21H1, 21H2, 31H1 and 31H2); Composite (11HZ1, 11HZ2, 21HZ1, 21HZ2, 31HZ1 and 31HZ2); Fiberboard (11G); Wooden (11C, 11D and 11F); Flexible (13H1, 13H2, 13H3,

13H4, 13H5, 13L1, 13L2, 13L3, 13L4, 13M1 or 13M2).

IP2 - When IBCs other than metal or rigid plastics IBCs are used, they must be offered for transportation in a closed freight container or a closed transport vehicle.

IP4 - Flexible, fiberboard or wooden IBCs must be sift-proof and water-resistant or be fitted with a sift-proof and water-resistant liner.

T3 - 2.65 178.274(d)(2) Normal..... 178.275(d)(2)

TP33 - The portable tank instruction assigned for this substance applies for granular and powdered solids and for solids which are filled and discharged at temperatures above their melting point which are cooled and transported as a solid mass. Solid substances transported or offered for transport above their melting point are authorized for transportation in portable tanks conforming to the provisions of portable tank instruction T4 for solid substances of packing group III or T7 for solid substances of packing group II, unless a tank with more stringent requirements for minimum shell thickness, maximum allowable working pressure, pressure-relief devices or bottom outlets are assigned in which case the more stringent tank instruction and special provisions shall apply. Filling limits must be in accordance with portable tank special provision TP3. Solids meeting the definition of an elevated temperature material must be transported in

accordance with the applicable requirements of this subchapter.

DOT Packaging Exceptions (49 CFR 173.xxx) 154 DOT Packaging Non Bulk (49 CFR 173.xxx) 212 DOT Packaging Bulk (49 CFR 173.xxx) 240 DOT Quantity Limitations Passenger aircraft/rail (49 : 15 kg

CFR 173.27)

DOT Quantity Limitations Cargo aircraft only (49

CFR 175.75)

**DOT Vessel Stowage Location** 

: 50 kg

: B - (i) The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel carrying a number of passengers limited to not more than the larger of 25 passengers, or one passenger per each 3 m of overall vessel length; and (ii) "On deck only" on passenger vessels in which the number of passengers specified in paragraph (k)(2)(i) of this

section is exceeded.

Emergency Response Guide (ERG) Number : 154

**IMDG** 

Special provision (IMDG) : 274 Limited quantities (IMDG) 1 kg Excepted quantities (IMDG) E2 Packing instructions (IMDG) P002 IBC packing instructions (IMDG) IBC08 B21. B4 IBC special provisions (IMDG) Tank instructions (IMDG) : T3 Tank special provisions (IMDG) : TP33

EmS-No. (Fire) : F-A - FIRE SCHEDULE Alfa - GENERAL FIRE SCHEDULE EmS-No. (Spillage) : S-B - SPILLAGE SCHEDULE Bravo - CORROSIVE SUBSTANCES

Stowage category (IMDG) : B

Segregation (IMDG) SGG1, SG36, SG49

Properties and observations (IMDG) Causes burns to skin, eyes and mucous membranes.

**IATA** 

: E2 PCA Excepted quantities (IATA) PCA Limited quantities (IATA) Y844 PCA limited quantity max net quantity (IATA) : 5kg

12/13/2022 (Issue date) EN (English US) 8/10

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

PCA packing instructions (IATA) : 859
PCA max net quantity (IATA) : 15kg
CAO packing instructions (IATA) : 863
CAO max net quantity (IATA) : 50kg
Special provision (IATA) : A3, A803
ERG code (IATA) : 8L

## 14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

# **SECTION 15: Regulatory information**

#### 15.1. US Federal regulations

All components of this product are present and listed as Active on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory, except for:

| Е | thylene sulfate | CAS-No. 1072-53-3 | 100% |
|---|-----------------|-------------------|------|
|   |                 |                   |      |

## 15.2. International regulations

#### **CANADA**

No additional information available

#### **EU-Regulations**

No additional information available

#### **National regulations**

No additional information available

## 15.3. US State regulations

California Proposition 65 - This product does not contain any substances known to the state of California to cause cancer, developmental and/or reproductive harm

# **SECTION 16: Other information**

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

| Full text of H-phrases |   |  |
|------------------------|---|--|
| H302                   | Harmful if swallowed                    |  |
| H314                   | Causes severe skin burns and eye damage |  |
| H318                   | Causes serious eye damage               |  |
| H335                   | May cause respiratory irritation        |  |

NFPA health hazard : 3 - Materials that, under emergency conditions, can cause serious or

permanent injury.

NFPA fire hazard : 1 - Materials that must be preheated before ignition can occur.

NFPA reactivity : 1 - Materials that in themselves are normally stable but can become unstable at elevated temperatures and pressures.

3 1

Hazard Rating

# Safety Data Sheet

Flammability

Physical

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Health : 3 Serious Hazard - Major injury likely unless prompt action is taken and medical treatment is

: 1 Slight Hazard - Materials that must be preheated before ignition will occur. Includes liquids, solids and semi solids having a flash point above 200 F. (Class IIIB)

: 1 Slight Hazard - Materials that are normally stable but can become unstable (self-react) at high temperatures and pressures. Materials may react non-violently with water or undergo hazardous polymerization in the absence of inhibitors.

Safety Data Sheet (SDS), USA

The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. The information in this document is based on the present state of our knowledge and is offered solely for your consideration, investigation, and verification. It does not represent any guarantee of the properties of the product nor that the hazard precautions or procedures described are the only ones which exist. SynQuest shall not be held liable or any damage resulting from handling or from contact with the above product.

12/13/2022 (Issue date) EN (English US) 10/10